Mini Filter Packages

Features:

- Liquids and Sub-micron
 Particulates Collect at the
 Bottom of the Element, protect downstream components form contamination.
- Poly Bowl.
- Disassembles Easily for Servicing without the use of Tools.

Twin Tower Engineering's miniature coalescing and particulate filters protect clean dry compressed air from water aerosols, liquid oil, scale, and dirt. These contaminants can cause malfunction or loss of drying efficiency.

These filter packages are matched to our miniature MDH-Series and MCA-Series compressed air dryer models in flow and performance. We can also size the filters to your existing dryer.

Each set includes two pre-filters (particulate and coalescing) to protect the air dryer from liquid water and oil, one after-filter (particulate) to protect downstream components. Also included are (2) 1/4" brass connecting nipples and wall mounting brackets.







Part #	Description	Ports	Flow	Max Inlet	PKG WT	Use for Dryers
		NPT	SCFM	PSIG	LB	MODEL
51820	STD PKG: (2) Pre-Filters, (1) After-Filter, (2) 1/4" Nipples	1/4"	8.0	0-50	1.3	MDH/MCA
51820–R	STD PKG + Regulator with Gauge, 0-125 PSIG Outlet	1/4"	8.0	0-150	2.0	MDH/MCA







(1) Prefilter, 5.0 Micron(1) Prefilter, 0.01 Micron

Typical Applications:

- Pneumatic Hand Tools
- Air Gauging
- Miniature Desiccant Air Dryers
- Membrane Air Dryers
- Instrument air & gas
- Pre-filter for deliquescent
- Regenerative dryers
- Refrigerated dryers
- Abrasive blasting
- Dust collectors
- Air cylinders, motors
- Blow molding

Element Replacement Kits			
Filter Kit	Element Kit		
51820	51975		
51820-R	51975		



(1) Afterfilter, 1.0 Micron

For additional information please go to our web site @ airdryers



PO BOX 879 2150 W. 6TH AVE UNIT P BROOMFIELD, CO 80020 TEL 800-700-8537 FAX 303-465-9294 SALES@AIRDRYERS.COM